



Registered in the U.S. Patent and Trademark Office

Sluice Stand Instructions



Item# 581



Item# 586



Registered in the U.S. Patent and Trademark Office

2801 East 12th Street | Los Angeles, CA 90023
phone 323.269.0510 | fax 323.269.2761



Set Up

1. *From new: Remove frame from box, noting this is in its original folded position.*
2. *Grasp frame in center with one hand. Holding the frame parallel to the ground, quickly release the bottom half of the frame so it swings downward and the spring clips are engaged into their locking holes. The frame should be locked rigid at this point. If not, apply light pressure to the spring clips to engage them into the locking holes.*
3. *Unscrew the stainless steel wing nuts from the four tube receivers.*
4. *Insert the two shorter 16" legs into the receivers at the exiting end next to the tabs and tighten wing nuts.*
5. *Insert the two longer 20" legs into the opposite end next to the snap clips and tighten wing nuts.*

6. *The holes at the base of the legs are intended to secure the frame to plywood for extended use.*

7. *Insert your 24" or 30" sluce box in the center of the frame.*

8. *Pick up the carpet slightly and slide sluce the under tabs. This holds the sluce box from sliding off the end.*

9. *Lift up the snap clips until they snap securely onto the top of the sluce box.*

Operating Sluce Instructions

1. *Refer to the Operating Instructions provided with your sluce box*

Storage

1. *Unlatch the frame by grasping both clips with your thumbs at the same time and pull outward.*
2. *Ensure the frame is in its original folded position. If the snap clips collide together, your frame is in the wrong position. To put the frame in the correct position, rotate the frame 360° in the opposite direction until the tubes are parallel.*

Helpful Hints

This folding frame was designed to enable us to ship the frame more cost effectively, but is not necessary to re-fold it.